Amortized Analysis

- Amortized Analysis
- Aggregate Method
- Accounting Method
- Potential Method

Philip Bille

Amortized Analysis

- Amortized Analysis
- Aggregate Method
- Accounting Method
- Potential Method

Amortized Analysis

- Motivating example.
  - Consider an algorithm A that consists of m operations on data structure D.
  - The individual operations on D vary in running time. Many are fast, but a few are slow.
  - How do we analyze A's running time?

- Standard analysis. Number of operations × worst-case time for an operation.

- Amortized analysis. Total time of all operations.



Amortized Analysis

- Amortized time complexity.
  - Let T(m) be the worst-case time complexity for any sequence of m operations on a data structure. The amortized time complexity of an operation is T(m)/m.



Amortized Analysis

- Applications.
  - Algorithms that use data structures. Total time is important, not individual operations.
    - Examples: Minimum spanning tree algorithms, Dijkstra's shortest path algorithm, ...
  - Simple and practical. Often simpler and faster than worst-case versions.

- Goals.
  - Techniques for showing bounds on amortized complexity.
  - New data structures and data structure design techniques.

Amortized Analysis

- Amortized Analysis
- Aggregate Method
- Accounting Method
- Potential Method

Aggregate Method

- Aggregate method.
  - Identify a worst-case sequence of m operations.
  - Compute the total time complexity T(m) of the sequence.
  - Compute T(m)/m as the amortized time complexity.

Stack

- Stack with MultiPop. Maintain a sequence (stack) S supporting the following operations:
  - PUSH(x): add x to S.
  - MULTIPOP(k): remove and return the k most recently added elements in S.
  - POP() = MULTIPOP(1).
- Assume POP/MULTIPOP always has enough elements on stack.



Stack

- Stack with MultiPop. Maintain a stack S supporting PUSH(x) and MULTIPOP(k).

- Consider a sequence of m operations.

- Standard analysis.
  - PUSH in O(1) time.
  - MultiPop in O(k) = O(m) time.

- Amortized analysis.
  - An element can only be POPped once for each time it is PUSHed.
  - ⇒ Total number of POPs is ≤ total number of PUSHes ≤ m.
  - ⇒ Total time is O(m)
  - ⇒ Amortized time of MULTIPOP is O(1).



Amortized Analysis

- Amortized Analysis
- Aggregate Method
- Accounting Method
- Potential Method

Amortized Analysis

- Actual cost. c_i = actual cost of operation i = time complexity of operation i.

- Amortized cost.
  - Assign a cost $\hat{c}_i$ to operation i.
  - $\hat{c}_i$ is an amortized cost for D if for all sequences $O = o_1, \ldots, o_m$.
  - $$\sum_{i=1}^{m} \hat{c}_i \geq \sum_{i=1}^{m} c_i.$$
- If $\hat{c}_i$ is an amortized cost ⇒ $\hat{c}_i$ is also amortized running time.



Accounting Method

- Accounting method.
  - Assign a cost $\hat{c}_i$ to each operation.
    - $\hat{c}_i > c_i$: store the difference as credits to objects in the data structure.
    - $\hat{c}_i < c_i$: use the stored credits to pay for operation.
  - Show that cost is an amortized cost ⇒ amortized cost is amortized running time.

- Challenge. How to find a good credit scheme?

Stack

- Stack with MultiPop. Maintain a stack S supporting PUSH(x) and MULTIPOP(k).

- Costs.
  - A credit pays for a PUSH or POP.
  - PUSH(x): use 1 credit to PUSH element. Assign 1 credit to element.
  - MULTIPOP(k): use stored credits on top k elements to pay.

	Actual Cost	Assigned Cost
PUSH	1	2
MULTIPOP	k	0

- Amortized analysis.
  - Always enough credits to pay for MULTIPOP.
  - $\Rightarrow \sum_{i=1}^{m} \hat{c}_i \geq \sum_{i=1}^{m} c_i$
  - $\Rightarrow$ Assigned cost are amortized costs.
  - $\Rightarrow$ Amortized running time of MULTIPOP is O(1).



Dynamic Ordered Sets

- Dynamic Ordered Sets. Maintain a dynamic set S of numbers supporting the following operations.
  - SEARCH(x): return true if $x \in S$.
  - PREDECESSOR(x): return the largest element in S that is $\leq x$.
  - SUCCESSOR(x): return the smallest element in S that is $\geq x$.
  - INSERT(x): add x to S.
  - DELETE(x): remove x from S.



Dynamic Ordered Sets

- Applications.
  - Dictionaries, indexes, databases, filesystem, ...

- What solutions do we know?

Dynamic Binary Search

- Dynamic binary search.
  - Maintain arrays $A_0, A_1, A_2, \ldots, A_{h-1}$. A^i has size 2^i and $h \approx \log(n)$.
  - Each array is either full or empty.
  - Full arrays correspond to the binary representation of $n = |S|$.
  - Each full array stores elements from S in sorted order.

$n = 23_{10} = 10111_2$



Dynamic Binary Search

- SEARCH(x): Do a binary search in each array.



$n = 23_{10} = 10111_2$

- Time. $O(\log^2 n)$.
- Similar idea for PREDECESSOR and SUCCESSOR.

Dynamic Binary Search

- INSERT(x):
  - If A_0 is empty, fill it with x and stop.
  - Create singleton array containing x. Merge arrays pairwise top-down until we fill empty array.
  - Corresponds to incrementing a binary number.



Dynamic Binary Search



- Standard analysis.
  - Create singleton array: O(1) time.
  - Merge arrays $A_0,\ldots,A_{k-1}$: $O(2^0 + 2^1 + \ldots + 2^k) = O(2^{k+1} - 1) = O(n)$ time.
  - $\Rightarrow$ O(n) time in total.

Dynamic Binary Search

- Observations.
  - Most insertions are fast.
  - Elements always start at top and move down monotonically.



$n = 23_{10} = 10111_2$



$n = 24_{10} = 11000_2$

Dynamic Binary Search

- Costs.
  - A credit pays for a single element being part of a merge.
  - INSERT(x): Assign h-1 credits to element. Use credits to pay for merges.





Dynamic Binary Search

- Amortized analysis.
  - Enough credits to pay for merges ⇒ assigned cost are amortized costs.
  - ⇒ Amortized running time of INSERT is h-1 = O(log n).



Dynamic Binary Search

- Dynamic binary search.
  - SEARCH, PREDECESSOR, and SUCCESSOR in $O(\log^2 n)$ time.
  - INSERT and DELETE in $O(\log n)$ amortized time.

- With fractional cascading technique we can do SEARCH, PREDECESSOR, and SUCCESSOR in $O(\log n)$ time.

- Key component in database indexes called a log-structured merge.
- General idea for transforming static data structures into dynamic data structures.

Amortized Analysis

- Amortized Analysis
- Aggregate Method
- Accounting Method
- Potential Method

Potential Method

$$D_0 \xrightarrow{o_1} D_1 \xrightarrow{o_2} D_2 \xrightarrow{o_3} D_3 \quad \cdots \quad D_{m-1} \xrightarrow{o_m} D_m$$

- Potential function.
  - Define a potential function $\Phi(D)$ that maps (the state of) data structure D to a real value.
  - Require that $\Phi(D_i) \geq 0$ for all i and $\Phi(D_0) = 0$.
  - Assign cost $\hat{c}_i = c_i + \Phi(D_i) - \Phi(D_{i-1})$.
  - Corresponds to potential energy.

- Amortized cost.
  - $\hat{c}_i$ is an amortized cost:
  - $$\sum_{i=1}^{m} \hat{c}_i = \sum_{i=1}^{m} \left(c_i + \Phi(D_i) - \Phi(D_{i-1})\right) = \sum_{i=1}^{m} c_i + \Phi(D_m) - \Phi(D_0) \geq \sum_{i=1}^{m} c_i$$

Potential Method

- Potential method.
  - Define a potential function $\Phi(D)$.
  - Compute the corresponding amortized cost $\Rightarrow$ amortized cost is amortized running time.

- Challenge. How to find a good potential function?

Stack

- Stack with MultiPop. Maintain a stack S supporting PUSH(x) and MULTIPOP(k).

- Potential function.
  - Define $\Phi(D_i)$ = number of elements on stack.
  - $\Phi(D_i) \geq 0$ for all i and $\Phi(D_0) = 0$.

- Amortized analysis.
  - PUSH(x): $\hat{c}_i = c_i + \Phi(D_i) - \Phi(D_{i-1}) = 1 + 1 = 2$.
  - MULTIPOP(k): $\hat{c}_i = c_i + \Phi(D_i) - \Phi(D_{i-1}) = k - k = 0$.
  - $\Rightarrow$ amortized running time of MULTIPOP is O(1).

Dynamic Binary Search

- Dynamic binary search.
  - Maintain arrays $A_0, A_1, A_2, \ldots, A_{h-1}$. A^i has size 2^i and $h \approx \log(n)$.
  - Each array is either full or empty.
  - Full arrays correspond to the binary representation of $n = |S|$.
  - Each full array stores elements from S in sorted order.

$n = 23_{10} = 10111_2$



Dynamic Binary Search

- Potential function. Let $b_{h-1}b_{h-2}\ldots b_0$ be the binary representation of n and define
- $$\Phi(D) = \sum_{j=0}^{h-1} b_j \cdot 2^j \cdot ((h-1)-j)$$
- Intuition. Individual elements have potential corresponding to their height.



$n = 23_{10} = 10111_2$

Φ

$b_0 \cdot 2^0 \cdot (h-1) = 1 \cdot 1 \cdot 4 = 4$

$b_1 \cdot 2^1 \cdot (h-2) = 1 \cdot 2 \cdot 3 = 6$

$b_2 \cdot 2^2 \cdot (h-3) = 1 \cdot 4 \cdot 2 = 8$

$b_3 \cdot 2^3 \cdot (h-4) = 0 \cdot 8 \cdot 1 = 0$

$b_4 \cdot 2^4 \cdot (h-5) = 1 \cdot 16 \cdot 0 = 0$

Dynamic Binary Search

- Amortized analysis (case 1). No merges.
  - Actual cost: $c_i = 1$.
  - Increase in potential:
  - $\Phi(D_i) - \Phi(D_{i-1}) = 2^0(h-1) = h - 1$

$$\Phi(D) = \sum_{j=0}^{h-1} b_j \cdot 2^j \cdot ((h-1) - j)$$

- Amortized cost.
  - $\hat{c}_i = c_i + \Phi(D_i) - \Phi(D_{i-1}) = 1 + h - 1 = h = O(\log n)$



Dynamic Binary Search

- Amortized analysis (case 2). Merge arrays $A_0,\ldots,A_{k-1}$.
  - Actual cost: $c_i = \sum_{j=0}^{k} 2^j = 2^{k+1} - 1.$
  - Decrease in potential:

$$\sum_{j=0}^{k-1} 2^j(k-j) = k \cdot \sum_{j=0}^{k-1} 2^j - \sum_{j=0}^{k-1} j \cdot 2^j$$

$$= k \cdot (2^k - 1) - \left((k-2)2^k + 2\right)$$

$$= 2^{k+1} - k - 2$$

$$\Phi(D) = \sum_{j=0}^{h-1} b_j \cdot 2^j \cdot ((h-1) - j)$$

- Amortized cost.

$$\hat{c}_i = c_i + \Phi(D_i) - \Phi(D_{i-1})$$

$$= 2^{k+1} - 1 - (2^{k+1} - k - 2) = k + 1 = O(\log n)$$



Dynamic Binary Search

- ⇒ Amortized running time of INSERT is O(log n) in both cases.

- Dynamic binary search.
  - SEARCH, PREDECESSOR, and SUCCESSOR in $O(\log^2 n)$ time.
  - INSERT and DELETE in O(log n) amortized time.

Amortized Analysis

- Amortized Analysis
- Aggregate Method
- Accounting Method
- Potential Method